



AESOLAR

since 2003



AURORA

HIGH ENERGY YIELD RELIABILITY DURABILITY

30
years

Performance
Warranty

15
years

Product
Warranty

430W-450W AE MC-144 Series

MONO-CRYSTALLINE PV MODULES
HALF-CUT CELLS • MONO-FACIAL

www.ae-solar.com

Ver. 23.12.1



HALF
CELLS



CELL
SIZE



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT



AMMONIA
RESISTANT



HIGHLY STABLE
AND TOUGH



IEC 61215 IEC 61730
Regular Production Surveillance
www.tuv.com
ID 1111251295



AE MC-144 Series 430W-450W



MONO-CRYSTALLINE PV MODULES
HALF-CUT CELLS • MONO-FACIAL

Mechanical and design specification




Cell type	Gallium-doped Mono c-Si PERC, Half-cut cells, 166 mm
No. of cells	144
Front cover	3.2 mm glass, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	White Backsheet
Junction box	IP68 rated, 3 Bypass Diodes
Frame	30 mm anodized Aluminium alloy
Cable	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2094 mm x 1038 mm x 30 mm
Weight	22 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m ²
Snow load	5400 Pa or 550 kg/m ²

Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	792 pcs / 40 HQ
Size / Pallet	2125 mm x 1140 mm x 1150 mm
Weight	850 kg / pallet

Temperature ratings

Operating temperature	(°C)	-40 to +85
Temp.coefficient of P _{max}	(%/°C)	-0.35
Temp.coefficient of V _{oc}	(%/°C)	-0.286
Temp.coefficient of I _{sc}	(%/°C)	0.057
Nom. operating temp. NOCT	(°C)	45 ± 2



Electrical specifications (STC*):		AE430MC-144	AE435MC-144	AE440MC-144	AE445MC-144	AE450MC-144
Nominal Max. Power	P _{max} (Wp)	430	435	440	445	450
Maximum operating voltage	V _{MPP} (V)	40.60	40.80	41.00	41.20	41.40
Maximum operating current	I _{MPP} (A)	10.60	10.67	10.74	10.80	10.87
Open-circuit voltage	V _{oc} (V)	49.20	49.40	49.60	49.80	50.00
Short-circuit current	I _{sc} (A)	11.19	11.26	11.33	11.46	11.54
Module efficiency	η (%)	19.78	20.01	20.24	20.47	20.70
Power tolerance	(W)			0~+5		
Maximum system Voltage	(V)			1500		
Maximum series fuse rating	(A)			20		

*STC: Standard test conditions (Irradiance 1000 W/m², Cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max}: ±3%

Electrical specifications (NMOT*):		AE430MC-144	AE435MC-144	AE440MC-144	AE445MC-144	AE450MC-144
Nominal Max. Power	P _{max} (Wp)	324	328	332	335	339
Maximum operating voltage	V _{MPP} (V)	38.20	38.40	38.60	38.80	39.0
Maximum operating current	I _{MPP} (A)	8.48	8.54	8.59	8.64	8.70
Open-circuit voltage	V _{oc} (V)	46.30	46.50	46.70	46.90	47.10
Short-circuit current	I _{sc} (A)	8.95	9.01	9.06	9.16	9.23

*NMOT: Normal Module Operating Temperature (Irradiance 800 W/m², Ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.



+216 98 366 669
contact@hydroelec-tn.com
www.hydroelec-tn.com/
Lot 68 Rue Khlidia zone industriel
Mghira lFouchena 2082 Ben anous, Tunis



+49 8231 978268 0
sales@ae-solar.com
www.ae-solar.com

AESOLAR
Messerschmittring 54
86343 Königsbrunn, Germany